

SUPPLEMENT TO

SCHEDULE (C).—PART II.—(See § 5.)

Concourse for determining the Rates to which Buildings of the First or Dwelling-House Class are to be deemed to belong, and the Thickness of the External and of the Party Walls thereof.

In reference to Height.	In reference to Area.	In reference to Stories.	State of Building.	Required Thickness of External Walls of each State of the First Class.	Required Thickness of Party Walls of each State of the First Class.
1. If the building be in height not more than 20 feet, or if it cover more than 64 square feet.	1. If the building be in height not more than 20 feet, or if it cover more than 64 square feet.	1. If the building contain more than 2 stories, or if it contains 2 stories and less than three stories, or if it contains 3 stories and less than four stories.	It is to be of the First or Lowest State.	And the thickness of the external walls must be, to the least, 6 <i>4</i> inches from the top of the footing to the top of the wall.	And the thickness of the party-walls must be, to the least, 15 <i>4</i> inches from the top of the footing to the top of the wall.
2. If more than 22, and not more than 25 feet, or if it cover more than 64 square feet, and less than three stories.	2. If more than 22, and not more than 25 feet, or if it cover more than 64 square feet, and less than three stories.	2. If it contains 3 stories, or if it contains 4 stories and less than five stories.	It is to be of the Second State.	And the thickness of the external walls must be, at the least, 17 <i>4</i> inches from the top of the footing to the under-side of the gutter-plate; and on the least 6 <i>4</i> inches from the under-side of the plate to the top of the wall.	And the thickness of the party-walls must be, at the least, 17 <i>4</i> inches from the top of the footing to the under-side of the second floor, and to the least 6 <i>4</i> inches from the under-side of the second floor to the top of the wall.
3. If more than 25, and not more than 30 feet, or if it cover more than 64 square feet.	3. If more than 25, and not more than 30 feet, or if it cover more than 64 square feet.	3. If it contains 5 stories, or if it contains 6 stories and less than seven stories.	It is to be of the Third State.	And the thickness of the external walls must be, at the least, 19 <i>4</i> inches from the top of the footing to the under-side of the second floor; and on the least 6 <i>4</i> inches from the under-side of the second floor to the top of the wall.	And the thickness of the party-walls must be, at the least, 19 <i>4</i> inches from the top of the footing to the under-side of the third floor; and, to the least, 6 <i>4</i> inches from the under-side of the third floor to the top of the wall.
4. If more than 32, and not more than 36 feet, or if it cover more than 64 square feet.	4. If more than 32, and not more than 36 feet, or if it cover more than 64 square feet.	4. If it contains 6 stories, or if it contains 7 stories and less than eight stories.	It is to be of the Fourth State.	And the thickness of the external walls must be, at the least, 21 <i>4</i> inches from the top of the footing to the under-side of the third floor; and on the least 6 <i>4</i> inches from the under-side of the third floor to the top of the wall.	And the thickness of the party-walls must be, at the least, 21 <i>4</i> inches from the top of the footing to the under-side of the fourth floor; and, to the least, 6 <i>4</i> inches from the under-side of the fourth floor to the top of the wall.
5. If more than 36, and not more than 40 feet, or if it cover more than 64 square feet.	5. If more than 36, and not more than 40 feet, or if it cover more than 64 square feet.	5. If it contains 7 stories, or if it contains 8 stories and less than nine stories.	It is to be of the Fifth State.	And the thickness of the external walls must be, at the least, 23 <i>4</i> inches from the top of the footing to the under-side of the fourth floor; and on the least 6 <i>4</i> inches from the under-side of the fourth floor to the top of the wall.	And the thickness of the party-walls must be, at the least, 23 <i>4</i> inches from the top of the footing to the under-side of the fifth floor; and, to the least, 6 <i>4</i> inches from the under-side of the fifth floor to the top of the wall.
6. If more than 42 feet, or if it cover more than 12 square feet.	6. If more than 42 feet, or if it cover more than 12 square feet.	6. If it contains more than six stories.	It is to be of the Sixth State, and of the First Class.	And the thickness of the external walls must be, at the least, 25 <i>4</i> inches from the top of the footing to the under-side of the fifth floor; and, to the least, 6 <i>4</i> inches greater than is hereby required for walls of the fifth rate.	And the thickness of the party-walls must be, at the least, 25 <i>4</i> inches greater than is hereby required for walls of the fifth rate.

FIRST, OR DWELLING-HOUSE CLASS.

